

Product Information

AVENO FS Excellence 0W-40

0002-000032



Description

AVENO FS Excellence 0W-40 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbo-charging and direct injection. AVENO FS Excellence 0W-40 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions. With AVENO FS Excellence 0W-40 a reliable and heavy-duty engine oil has been developed to guarantee the low viscosity of SAE 0W-class as well as a low evaporation loss.

Instructions for use

AVENO FS Excellence 0W-40 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. AVENO FS Excellence 0W-40 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- ACEA A3/B4
- API SP
- API CF

Approval

- API SP
- MB-Freigabe 229.5
- Renault RN0710
- VW 502 00/505 00
- Porsche A40

Recommendation

- BMW Longlife-01
- Fiat 9.55535-M2/-Z2
- Ford WSS-M2C937-A
- Renault RN0700
- MB 226.5
- MB 229.3
- PSA B71 2296

Properties

- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters
- Excellent cold starting properties, even at low temperatures below -30°
- A very stable and excellent viscosity behavior and shear stability
- Excellent protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	77.4	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	13.8	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	185		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -35°C	5820	mPa*s	ASTM D 5293:2020
Density at 15°C	844	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-54	°C	ASTM D 7346:2015
Total Base Number (TBN)	11.5	mgKOH/g	ASTM D 2896:2015