

# Product Information

## AVENO Maxi Fuel Economy 0W-16 GREEN

0002-000053



### Description

AVENO Maxi Fuel Economy 0W-16 GREEN is a fully synthetic low-friction engine oil for passenger car gasoline and diesel engines with and without turbocharging and direct injection. AVENO Maxi Fuel Economy 0W-16 GREEN is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear. Extended oil change intervals according to the manufacturer's instructions.

### Instructions for use

AVENO Maxi Fuel Economy 0W-16 GREEN is ideally suited for energy-saving year-round use in all modern passenger car gasoline and diesel engines. It thus reduces CO<sup>2</sup> emissions and helps protect the environment. AVENO Maxi Fuel Economy 0W-16 GREEN is used in engines with the specified specifications. The operating regulations of the vehicle and engine manufacturers must be observed.

### Quality classification

#### Specification

- API SQ
- ILSAC GF-7B

#### Recommendation

- Honda 08215-99974, Honda 08216-99974
- Honda 08232-P99S1LHE, Honda Ultra Next/Ultra Green
- Hybrid Engine Nissan KLANM-01A04 Extra Save X Eco
- Mitsubishi Diaqueen ECO Plus
- Mitsubishi MZ102661, Mitsubishi MZ102662
- Toyota 08880-11005

### Properties

- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealing materials
- Catalyst suitability
- Extended oil change intervals protect natural resources
- Excellent cold start properties even at low temperatures
- An extremely stable and excellent viscosity behavior, shear stability
- Low evaporation tendency, therefore low oil consumption
- Excellent protection against wear, corrosion and foam formation

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	39.1	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7.3	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	154		DIN ISO 2909:2004-08
Appearance	GREEN		VISUELL
Viscosity CCS at -35°C	4410	mPa*s	ASTM D 5293:2020
Density at 15°C	842	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-66	°C	ASTM D 7346:2015
Total Base Number (TBN)	8.1	mgKOH/g	ASTM D 2896:2015