

# Product Information

## AVENO MTF-3 SAE 75W

0002-000163



### Description

AVENO MTF-3 SAE 75W is a synthetic smooth-running gear oil for special manual gearboxes. AVENO MTF-3 SAE 75W is designed on a basis of synthetic base oils and specially coordinated additives. This ensures compliance with today's practical requirements is exceeded. AVENO MTF-3 SAE 75W is excellently suited for very high mechanical and thermal stress in manual gearbox oils, even under the longest oil-change intervals.

### Instructions for use

AVENO MTF-3 SAE 75W is ideally suited for very high mechanical and thermal loads on manual transmission oils, even with the longest oil change intervals. It was developed for various gearboxes from car manufacturers such as Audi, Citroen, Mercedes-Benz, Mitsubishi, Nissan, Peugeot, Porsche, Seat, Skoda and Volkswagen.

### Quality classification

#### Specification

- API GL-4

#### Recommendation

- Honda MTF-3
- MB 235.10
- Mitsubishi MZ320065 Diaqueen SSTF-I
- Peugeot/Citroën 9734.S2
- AUDI G 055 532 A2
- VW G 052 171 A2, VW G 052 178 A2
- VW G 052 512 A2, VW G 055 726 A2

### Properties

- A very good viscosity-temperature behavior
- A high oxidation resistance
- A very good wear protection, excellent EP qualities
- A low tendency to foam, even at high speeds
- An extended lifespan
- A high-pressure stable lubrication film, even at high oil temperatures and stress
- An outstanding shear stability and an excellent thermal stability
- A good switching behavior, even at low temperatures, extremely low pour point
- A stable lubrication film, even at high oil temperatures and under high stress

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	37,2	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7.5	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	174		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	848	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015