Product Information

AVENO Zentral Hydraulik Fluid GREEN

0002-000257



Description

AVENO Zentral Hydraulik Fluid is a special hydraulic oil on the basis of synthetic oils with high-quality additives. Thanks to its special formulation, the properties of AVENO Zentral Hydraulik Fluid play a crucial role. We guarantee an excellent cold stability. AVENO Zentral Hydraulik Fluid has a high performance as a central hydraulic oil in power steering, rear axle for hydrostatic drive of ventilators, alternators and air conditioning systems, for stability and traction systems (ABS/ASR/ASC), central locking, electro-hydraulic convertible top controls, hydraulic brake boosters and hydropneumatic suspension for VW, Audi, Seat and Skoda. Especially for use in cold countries.

Instructions for use

AVENO Zentral Hydraulik Fluid is designed for use from -60°C to +130°C and is therefore recommended for the latest developments on the automotive market.

Recommendation

- Land Rover Cold Climate PAS Fluid 14315
- MB 343.0
- Opel 1940 766
- PSA B71 2710

- Peugeot/Citroën 9979 A1
- SAAB 93 160 548
- VOLVO 30741424
- VW G 004 000

Properties

- Reliable protection against corrosion
- Improved viscosity and friction behavior
- · An excellent thermal stability
- Neutral towards sealing agents

- Extremely low pour point
- A very good wear protection
- A good foaming behavior

| Technical specifications | | | |
|------------------------------|-------------------|-------|--------------------------|
| Properties | Data | Unit | Testing under |
| Kinematic Viscosity at 40°C | 25.3 | mm²/s | DIN 51659-2:2017-02 |
| Kinematic Viscosity at 100°C | 7.1 | mm²/s | DIN 51659-2:2017-02 |
| Viscosity Index | 267 | | DIN ISO 2909:2004-08 |
| Appearance | GREEN FLOURESCENT | | VISUELL |
| Density at 15°C | 840 | kg/m³ | DIN EN ISO 12185:1997-11 |
| Pour Point | -66 | °C | ASTM D 7346:2015 |