

Product Information

AVENO Circulating Oil CL 680

0002-000273



Description

A mild additive and is therefore particularly suitable for old machines. A good wear protection. Inhibits rust and corrosion and protects against ferrous metal corrosion. Prevents foam formation. Good water separation characteristics. AVENO Circulating Oil CL 680 is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of active ingredients, it is suitable for use as a simple machine lubricant where no EP-additive oils are required.

Instructions for use

AVENO Circulating Oil CL 680 has very good properties as a lubricant. Therefore AVENO Circulating Oil CL 680 can preferably be used for industrial gears and circulation systems of low and medium loads, where lubricants are required in accordance with DIN 51517-2.

Quality classification

Specification

- DIN 51517-2 (CL)

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	685.4	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	44.8	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	111		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	908	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-9	°C	ASTM D 7346:2015