

# Product Information

## AVENO DXS 5W-20

0002-000744



### Description

AVENO DXS 5W-20 is a synthetic smooth-running engine oil for petrol car engines with or without turbocharging and direct injection. AVENO DXS 5W-20 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions.

### Instructions for use

AVENO DXS 5W-20 is an energy-efficient engine oil for year-round use, and is ideal for modern petrol car engines. According to Dexos1 Gen3 specification it is recommended for General Motors under all operating conditions. The operating instructions of the car and engine manufacturers must be observed.

### Quality classification

#### Specification

- API SN Plus
- API SP (RC)
- ILSAC GF-5/GF-6A
- API SQ (RC)
- ILSAC GF-7A

#### Recommendation

- Chrysler MS-6395
- dexos1™ Gen3
- Ford WSS-M2C945-B1
- Ford WSS-M2C960-A

### Properties

- Fuel savings under all operating conditions
- Neutrality towards sealants
- Suitable for catalytic converters
- High oxidation stability
- Excellent cold starting properties
- A very stable and excellent viscosity behavior and shear stability
- Very good detergent and dispersing properties
- Excellent protection against wear, corrosion and foaming
- A secure lubricant film at very high operating temperatures

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	48.7	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	8.6	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	157		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	855	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Flash Point	244	°C	DIN EN ISO 2592:2018-01
Pour Point	-45	°C	ASTM D 7346:2015